

Related Document – No modification permitted without reference to the authorized person

Baserad på "PS_DOW_rev25_140520_LRW" , "MASTER BOM DOW R3 20130215", och "Instrument specification limit switch box 140612 Pmv Dow_rev8_2"

PS/PM switchbox Order code DOW

A= Brand sticker

D DOW

B= Rating Selection

N North American Standards, Special Marker Strip 3/4" NPT
 C Europe Standards, 2 cable Glands, Special Marker strip 1/2" NPT

C= Housing Selection

A Aluminium
 P Engineered resin

DxP DxA

D= Indicator Selection

1 No indicator - Flat top
 3 Ultra dome
 5 Ultradome indicator for 155 Degree Diverter Valves
 6 Ultradome indicator for 135 Degree Diverter Valves

E= Language Selection

0 No Indication
 D Dutch
 E English
 G German
 P Portuguese
 S Spanish
 I Italian

F= Switch Selection

B Phazer BRS™ (Not when B=C and G=1)
 K Phazer™ (Not when B=C and G=1)
 S P&F NJ2-V3-N
 M P&F NBB3-V3-Z4-3G-3D
 T Phazer BRS™
 P Phazer™

G= Area Selection

1 Standard
 2 Intrinsically safe

H= Mounting selection

N NAMUR Configuration, Namur Shaft
 STD Non-NAMUR configuration, "Standard Shaft"

I= Bracket and Fastener Selection

"" Empty cell
 28A NAMUR Shaft Flats, EL-O-Matic E25-E350, Hytork XL45-XL680, Air Torque PT050-PT300, UNC10-24
 28L NAMUR Shaft Flats, EL-O-Matic E25-E350, Hytork XL45-XL680, Air Torque PT050-PT300, M5 Fasteners
 38A NAMUR Shaft Flats, Air Torque PT350-PT500, UNC 10-24 See note 1
 38L NAMUR Shaft Flats, Air Torque PT350-PT500, M5 Fasteners See note 1
 313A NAMUR Shaft Flats, EL-O-Matic P500-P4000, Hytork XL1125-XL4580, UNC 10-24
 313L NAMUR Shaft Flats, EL-O-Matic P500-P4000, Hytork XL1125-XL4580, M5 Fasteners
 513A NAMUR Shaft Flats, Air Torque, PT550-PT800, UNC 10-24 See note 1
 513L NAMUR Shaft Flats, Air Torque, PT550-PT800, M5 Fasteners See note 1

Example

D	B	C	D	E	F	G	H	I
---	---	---	---	---	---	---	---	---