

APEX 7000 Electro pneumatic positioner

A= Prefix

Blank Automax

A Accord

B= Model

70 Pneumatic 3-15 psi input signal

71 Electro pneumatic 4-20mA

72 Explosion proof ATEX/VIEC/FM IIB + H2

74 Intrinsically safe ATEX/VIEC/CSA/FM

C= Indication

1 Flat green/black flag indicator

2 Ultra dome red/green indicator

D= Gauges

3 No gauges

4 Standard gauges (SST/brass)

E= Spool valves

6 Low flow spool valve

7 High flow spool valve

F= Cam type

A Standard 90 / 180 deg linear cam D/R

B 30 / 60 linear cam D & R

C Characterized Cam, Square root / =% D/R

D 60/120 linear cam D & R

G= Options

R Namur Shaft - Tuftram R66

T Namur Shaft - Standard ED coating

Q Namur Shaft - Silicone seals -40 deg C/F

D Double "D" 1/4" shaft - Standard ED coating

U Double "D" 1/4" shaft - Tuftram R66

V Double "D" 1/4" shaft - Silicone seals -40 deg C/F

Z Namur Shaft - Tuftram R66, Oxygen service (B = 70 only)

(*)
(*)
(*)
(*)

H= Feedback options

0 None

T Top mounted ultra switch kit KM7TOP p/n: 40615

A	B	C	D	E	F	G	H
----------	----------	----------	----------	----------	----------	----------	----------

*(For B=72 - IP PT32 is polyester coated and internal seals are Nitrile)