

**APEX 9000 Electro pneumatic positioner**

**A= Prefix**

- AX Automax
- AC Accord
- WC Worcester Controls


**B= Model**

- 90 Digital Positioner, Single button Interface, LED Status
- 92 Digital Positioner, Full LCD Menu, LED Status


**C= Approvals, Certifications**

- E Explosion proof ATEX / FM
- F FM
- N NEPSI / CCC


**D= Connections Air, Electrical**

- M 1/4" NPT air - M20 x 1,5 electrical
- N 1/4" NPT air - 1/2" NPT Electrical


**E= Housing / Surface treatment**

- U Aluminium / Powder Epoxy / Black
- R Remote mount (position sensing unit sold separately)
- Y Other


**F= Function**

- S Single Acting

--

**G= Shaft**

- 23 Namur shaft Rotary

--

**E= Cover (no indicator option on Explosion proof version)**

- 1 Flat top, no indicator

--

**F= Temperature / Seals**

- Z Standard -20C to +85C (-4F to 185F)
- Q Low temperature -40C to +85C (-40F to 185F)


**G= Input signal / Protocoll**

- N 4-20mA / None
- H 4-20mA / HART


**H= Feedback options**

- X No feedback option
- T 4-20 mA transmitter only


**I= Feedback Options, Add in Electronics**

- 0 Standard Diagnostics
- 1 Advanced, built in pressure sensors (Model 92 only)


**J= Accessories**

- X Gauge ports only, plugged
- N 2 x gauge 0-11 bar stainless/brass


A	B	C	D	E	F	G	H	I	J
---	---	---	---	---	---	---	---	---	---