

D20 Explosion Proof Digital Positioner Order Code

Rev 23 2021-03-09

	D20E	D22E
A = Model no		
D 2 0 Digital compact positioner, Single button interface, LED status		
D 2 2 Digital positioner, full LCD menu, LED status		
B = Approval, Certificate		
E Explosion proof ATEX/FM		
E F FM		
E N NEPSI / CCC		
C = Connections Air, Electrical		
G 1/4" G air, M20 x 1,5 electrical x 2		
M 1/4" NPT air, M20 x 1,5 electrical x 2		
N 1/4" NPT air, 1/2" NPT electrical x 2		
D = Housing/Surface treatment		
U Alu./Powder epoxy, black		
R Alu./Powder epoxy, black, Prepared for remote mounted feedback sensor		
E = Function		
S Single acting		
F = Mounting options / Spindle		
0 9 Double D type 6 mm, adaptor spindle (01/06/26/30/36)		
2 3 VDI/VDE 3845 rotary, (Mounting kit not included)		
3 0 1/2" square		
3 9 IEC 534-6, D style + nut. (Mounting kit not included)		
G = Cover Color		
P V B PMV, Black cover, No indicator		
F S W Flowserve White, No indicator		
F S Y Flowserve Yellow, No indicator		
H = Temperature/seals		
Z Standard -20°C to 85°C (-4°F to 185°F)		
Q Low temp -40°C to 85°C (-40°F to 185°F)		
I = Input signal/Protocol		
4 4-20 mA / none		
5 4-20 mA, / HART		
P Profibus PA		
F Foundation Fieldbus		
J = Feedback option, 4-20 mA transmitter, switches		
X No feedback option		
T 4-20 mA transmitter, Alarm output		
K = Options, Add in electronics		
0 Standard diagnostics		
1 Advanced, Built in pressure sensors		
L = Accessories		
X No accessories (gauge ports included)		
M Gauge block 1/8" G (2 x gauges included)		
N Gauge block 1/8" NPT (2 x gauges included)		

A
A
A
B
C
D
-
E
F
F
G
G
G
-
H
I
J
K
L

A
A
A
B
B
C
D
-
E
F
F
G
G
G
-
H
I
J
K
L

Consult factory