

D20 Compact Digital Positioner Order Code

	D20	D22
A = Model no		
D20 Digital compact positioner, Single button interface, LED status		
D22 Digital positioner, full LCD menu, LED status		
B = Approval, Certificate		
D General purpose version		
I Intrinsically safe version ATEX/FM		
C = Connections Air, Electrical		
M 1/4" NPT air, M20 x 1,5 electrical x 2		
N 1/4" NPT air, 1/2" NPT electrical x 2		
D = Housing/Surface treatment		
U Aluminium/Powder epoxy, black		
R Remote mounted feedback (position sensing unit sold separately)		
E = Function		
S Single acting		
D Double acting, Bolt on module incl 2 x gauges Stainlees/Brass (L≠N)		
F = Mounting options / Spindle		
09 Double D type, adaptor spindle		
12 Flowtop, direct mounting, Kit 30144 included		
23 VDI/VDE 3845 rotary, Mounting kit not included		
30 Adaptor spindle, select between 01/02/06/21/26/30/36		
39 IEC 534-6, Flat D type, nut incl. Mounting kit not included		
40 VDI/VDE 3847 Linear, Flat D, Mounting kit 30145 incl. (Not when E = D)		
G = Cover and Indicator		
PVA PMV, Black cover, Arrow indicator		
PVB PMV, Black cover, No indicator		
PVD PMV, Black cover, Dome indicator		
PVY A. Hock version, no indicator, EP2500-00 (E = S only)		
H = Temperature/seals		
Z Standard -20°C to 85°C (-4°F to 185°F)		
Q Low temp -40°C to 85°C (-38°F to 185°F)		
I = Input signal/Protocol		
4 4-20 mA / none		
5 4-20 mA, / HART		
P Profibus PA		
F Foundation Fieldbus		
J = Feedback option, 4-20 mA transmitter, switches		
X No feedback option		
T 4-20 mA transmitter only		
S Limit switches Mechanical SPDT + 4-20mA		
N Namur V3 type sensor, P+F NJ2-V3-N + 4-20mA		
P Limit switches Proximity SPDT + 4-20mA		
5 Slot type Namur sensor, P+F SJ2-SN + 4-20mA		
6 Slot type Namur sensor, P+F SJ2-N + 4-20mA		
K = Options, Add in electronics		
0 Standard diagnostics		
1 Advanced, Built in pressure sensors		
L = Accessories		
X No accessories		
N Gauge block 1/8" NPT (2 x gauges included, p/n 30447)		

A
A
A
B
C
D
-
E
F
F
G
G
G
-
H
I
J
K
L