

## D30 Digital Positioner Order Code

**A = Model no**

D 3 0 full LCD menu, LED status

**B = Approval, Certificate**

- D General purpose version
- E Intrinsically Safe Ex ia IECEx
- A Intrinsically Safe Ex ia ATEX
- B Intrinsically Safe Ex ia INMETRO
- N Intrinsically Safe Ex ia CCC
- M Intrinsically Safe Ex ia CCOE
- F Intrinsically Safe Ex ia FM

  
  
  
  
  
  


**C = Function**

H High Flow - Single/double acting - Spool valve

**D = Connections Air, Electrical**

- G 1/4" G air, M20 x 1,5 electrical
- M 1/4" NPT air, M20x1,5 electrical
- N 1/4" NPT air, 1/2"NPT electrical

  
  


**E = Connection feature**

- 2 2 Electrical conduits
- T 2 Electrical conduits, threaded Aux. ventilation

  


**F = Housing material/ Surface treatment**

U Aluminium/Powder epoxy, black

**G = Mounting options / Shaft**

- R M Remote mounting (position sensing unit sold separately)
- 0 9 Double D type, adaptor spindle
- 2 1 NAF shaft, including Mounting bracket D4-As920
- 2 3 VDI/VDE 3845 rotary, Mounting kit not included
- 3 0 Adaptor shaft, select between 01/06/26/30/36
- 3 9 IEC 534-6, Flat D type, nut incl. Mounting kit not included

  
  
  
  
  


**H = Cover and Indicator**

- P V A PMV, Black cover, Arrow indicator (Not RM units)
- P V B PMV, Black cover, No indicator
- F W A Flowserve, White, Arrow indicator (Not RM units)
- F W B Flowserve, White, No indicator

  
  
  


**I = Temperature/seals**

U -40°C to 80°C

**J = Input signal/Protocoll**

- 4 4-20 mA / none
- 5 4-20 mA, / HART
- P Profibus PA (Not for K=T)
- F Foundation Fieldbus (Not for K=T)

  
  
  


**K = Feedback option, switches**

- X No Feedback option (Only when J = P or F)
- T 4-20 mA transmitter only
- S Limit switches Mechanical SPDT + 4-20mA transmitter
- N Namur V3 type sensor, P+F NJ2-V3-N + 4-20mA transmitter
- P Limit switches Proximity SPDT + 4-20mA transmitter
- 5 Slot type Namur sensor, P+F SJ2-SN + 4-20mA transmitter
- 6 Slot type Namur sensor, P+F SJ2-N + 4-20mA transmitter

  
  
  
  
  
  


**L = Options, Add in electronics**

- 0 No pressure sensors
- 3 3 pressure sensors for advanced diagnostics

  


**M = Accessories**

- X No accessories
- M Gauge block 1/4" G (DA, 3 gauges included)
- N Gauge block 1/4" NPT (DA, 3 gauges included)

  
  


**N= Special Options**

- N No special options
- S Exhaust silencers
- T 270 deg rotary version (no shaft spring)
- U 270 deg rotary version (no shaft spring) + Exhaust silencers

  
  
  


**A A A B C D E** - **F G G H H H** - **I J K L M N**