

D30 Digital Positioner Order Code

- A = Model no**
D 3 0 full LCD menu, LED status
- B = Approval, Certificate**
D General purpose version
E Intrinsically Safe Ex ia IECEX
A Intrinsically Safe Ex ia ATEX
B Intrinsically Safe Ex ia INMETRO
N Intrinsically Safe Ex ia CCC
M Intrinsically Safe Ex ia CCOE
F Intrinsically Safe Ex ia FM
- C = Function**
H High Flow - Single/double acting - Spool valve
- D = Connections Air, Electrical**
G 1/4" G air, M20 x 1,5 electrical
M 1/4" NPT air, M20x1,5 electrical
N 1/4" NPT air, 1/2"NPT electrical
- E = Connection feature**
2 2 Electrical conduits
T 2 Electrical conduits, threaded Aux. ventilation
- F = Housing material/ Surface treatment**
U Aluminium/Powder epoxy, black
- G = Mounting options / Shaft**
R M Remote mounting (position sensing unit sold separately)
0 9 Double D type, adaptor spindle
2 1 NAF shaft, including Mounting bracket D4-As920
2 3 VDI/VDE 3845 rotary, Mounting kit not included
3 0 Adaptor shaft, select between 01/06/26/30/36
3 9 IEC 534-6, Flat D type, nut incl. Mounting kit not included
- H = Cover and Indicator**
P V A PMV, Black cover, Arrow indicator **(Not when G = RM)**
P V B PMV, Black cover, No indicator
F W A Flowserve, White, Arrow indicator **(Not when G = RM)**
F W B Flowserve, White, No indicator
H K B Hock version EP2500 Orange, no indicator
- I = Temperature/seals**
U -40°C to 80°C
- J = Input signal/Protocoll**
4 4-20 mA / none
5 4-20 mA, / HART
P Profibus PA
F Foundation Fieldbus
- K = Feedback option, switches**
X No Feedback option
T 4-20 mA transmitter only **(Only when J = 4 or 5)**
S* Limit switches Mechanical SPDT + 4-20mA transmitter
N* Namur V3 type sensor, P+F NJ2-V3-N + 4-20mA transmitter
P* Limit switches Proximity SPDT + 4-20mA transmitter
5* Slot type Namur sensor, P+F SJ2-SN + 4-20mA transmitter
6* Slot type Namur sensor, P+F SJ2-N + 4-20mA transmitter
- L = Options, Add in electronics**
0 No pressure sensors
3 3 pressure sensors for advanced diagnostics
- M = Accessories**
X No accessories
M Gauge block 1/4" G (DA, 3 gauges included)
N Gauge block 1/4" NPT (DA, 3 gauges included)
- N= Special Options**
N No special options
S Exhaust silencers
T 270 deg rotary version (no shaft spring)
U 270 deg rotary version (no shaft spring) + Exhaust silencers

A A A B C D E - **F G G H H H** - **I J K L M N**