

## F5 feedback unit order code

<b>A= Model No</b>	F 5 Feedback unit, to be installed on top of P5/EP5, no cover incl.	<b>F5</b> <input style="width: 50px; height: 20px;" type="text"/>
<b>B= Electrical connection</b>	G 2 x M20 x 1,5	<input style="width: 50px; height: 20px;" type="text"/>
	N 2 x 1/2" NPT	<input style="width: 50px; height: 20px;" type="text"/>
<b>C= Surface treatment</b>	U Epoxy, ED	<input style="width: 50px; height: 20px;" type="text"/>
	M Tuftram <b>(B=N only)</b>	<input style="width: 50px; height: 20px;" type="text"/>
<b>D= Switches</b>	M E C 2 x SPDT switches	<input style="width: 50px; height: 20px;" type="text"/>
	N A M 2 X Namur sensors	<input style="width: 50px; height: 20px;" type="text"/>
	P X Y 2 x SPDT proximty switches	<input style="width: 50px; height: 20px;" type="text"/>
<b>E= Feedback</b>	X X X None	<input style="width: 50px; height: 20px;" type="text"/>
	P O T Potentiometer, 5 kOhm	<input style="width: 50px; height: 20px;" type="text"/>
	P 1 K Potentiometer, 1 kOhm	<input style="width: 50px; height: 20px;" type="text"/>
	P 1 8 Potentiometer, 180 deg	<input style="width: 50px; height: 20px;" type="text"/>
	P 2 7 Potentiometer 270 deg	<input style="width: 50px; height: 20px;" type="text"/>
	4 2 0 4-20 mA transmitter	<input style="width: 50px; height: 20px;" type="text"/>
	T 1 8 4-20 mA transmitter, 180deg	<input style="width: 50px; height: 20px;" type="text"/>
	T 2 7 4-20 mA transmitter, 270 deg	<input style="width: 50px; height: 20px;" type="text"/>
<b>F= Spindle</b>	0 0 For installation on P5/EP5, no other spindle available.	<input style="width: 50px; height: 20px;" type="text"/>
<b>G= Temperature</b>	Z Nitrile, NBR -40 to +85 deg C	<input style="width: 50px; height: 20px;" type="text"/>

F  5   - 
      - 
  0  0 - 
  Z