

D20 Digital Positioner Order Code

A =	Model no		
	D 2 0	Single button interface, LED status	<input type="checkbox"/>
	D 2 1	Single button interface, LED status and LCD	<input type="checkbox"/>
	D 2 2	Full LCD menu, 5 button UI, LED status	<input type="checkbox"/>
B =	Approval, Certificate		
	D	General purpose version	<input type="checkbox"/>
	A	Intrinsically Safe Ex ia ATEX	<input type="checkbox"/>
	B	Intrinsically Safe Ex ia INMETRO	<input type="checkbox"/>
	N	Intrinsically Safe Ex ia CCC	<input type="checkbox"/>
	M	Intrinsically Safe Ex ia CCOE	<input type="checkbox"/>
	F	Intrinsically Safe Ex ia FM	<input type="checkbox"/>
C =	Function		
	S	SA D20 E/P (poppet valve)	<input type="checkbox"/>
D =	Connections Air, Electrical		
	M	1/4" NPT air, M20x1,5 electrical	<input type="checkbox"/>
	N	1/4" NPT air, 1/2"NPT electrical	<input type="checkbox"/>
E =	Connection feature		
	2	2 Electrical conduits	<input type="checkbox"/>
	T	2 Electrical conduits, threaded Aux. ventilation	<input type="checkbox"/>
F =	Housing material/ Surface treatment		
	U	Aluminium/Powder epoxy, black	<input type="checkbox"/>
G =	Mounting options / Shaft		
	R M	Remote mounting (position sensing unit sold separately)	<input type="checkbox"/>
	0 9	Double D type, adaptor spindle	<input type="checkbox"/>
	1 2	Flowtop, direct mounting, D4-As909m(D20) included	<input type="checkbox"/>
	2 3	VDI/VDE 3845 rotary, Mounting kit not included	<input type="checkbox"/>
	3 0	Adaptor shaft, select between 01/06/26/ 30/36	<input type="checkbox"/>
	3 9	IEC 534-6, Flat D type, nut incl. Mounting kit not included	<input type="checkbox"/>
H =	Cover and Indicator		
	P V A	PMV,Black cover, Arrow indicator	(Not RM unit) <input type="checkbox"/>
	P V B	PMV, Black cover, No indicator	<input type="checkbox"/>
	F W A	Flowserve, White, Arrow indicator	(Not RM unit) <input type="checkbox"/>
	F W B	Flowserve, White, No indicator	<input type="checkbox"/>
I =	Temperature/seals		
	Z	-20°C to 85°C (-4°F to 185°F)	<input type="checkbox"/>
J =	Input signal/Protocol		
	4	4-20 mA / none	<input type="checkbox"/>
	5	4-20 mA, / HART	<input type="checkbox"/>
	P	Profibus PA	(Not when K=T) <input type="checkbox"/>
	F	Foundation Fieldbus	(Not when K=T) <input type="checkbox"/>
K =	Feedback option, switches		
	X	No feedback option	<input type="checkbox"/>
	T	4-20 mA transmitter only (J = 4,5)	<input type="checkbox"/>
	S	Limit switches Mechanical SPDT	<input type="checkbox"/>
	N	Namur V3 type sensor, P+F NJ2-V3-N	<input type="checkbox"/>
	P	Limit switches Proximity SPDT	<input type="checkbox"/>
	5	Slot type Namur sensor, P+F SJ2-SN	(Not RM unit) <input type="checkbox"/>
	6	Slot type Namur sensor, P+F SJ2-N	(Not RM unit) <input type="checkbox"/>
L =	Options, Add in electronics		
	0	No pressure sensors	<input type="checkbox"/>
M =	Accessories		
	X	No accessories	<input type="checkbox"/>
	N	Gauge block 1/4" NPT (2 gauges included)	<input type="checkbox"/>
N=	Special Options		
	N	No special options	<input type="checkbox"/>
	T	270 deg rotary version (no shaft spring)	<input type="checkbox"/>

A A A B C D E - F G G H H H - I J K L M N