

APEX 9000 Electro pneumatic positioner

A= Prefix

AX Automax

WC Worcester Controls

B= Model

90 Digital Positioner, Single button Interface, LED Status

92 Digital Positioner, Full LCD Menu, LED Status

C= Approvals, Certifications

E Explosion proof ATEX / FM

F FM

N NEPSI / CCC

D= Connections Air, Electrical

M 1/4" NPT air - M20 x 1,5 electrical

N 1/4" NPT air - 1/2" NPT Electrical

E= Housing / Surface treatment

U Aluminium / Powder Epoxy / Black

S Stainless steel, Explosion proof (N connections only)

F= Function

S Single Acting

--

G= Shaft

23 Namur shaft Rotary

--

E= Cover (no indicator option on Explosion proof version)

1 Flat top, no indicator

--

F= Temperature / Seals

Z Standard -20C to +85C (-4F to 185F)

Q Low temperature -40C to +85C (-40F to 185F)

G= Input signal / Protocoll

N 4-20mA / None

H 4-20mA / HART

H= Feedback options

X No feedback option

T 4-20 mA transmitter only

I= Feedback Options, Add in Electronics

0 Standard Diagnostics

--

J= Accessories

X Gauge ports only, plugged

N 2 x gauge 0-11 bar stainless/brass

A	B	C	D	E	F	G	H	I	J
---	---	---	---	---	---	---	---	---	---